



THE STANDARD IN DIRECTIONAL CORE DRILLING

DRILL ROD DATA

Size	I.D.		O.D.		Weight/10'	
	inch	mm	inch	mm	Kg	Lbs
AWL	1.375	34.9	1.750	44.5	14.04	31
ATW	1.437	36.5	1.750	44.5	12.05	26.6
BWL	1.812	46.0	2.188	56.6	18.12	40
BTW	1.909	48.5	2.225	56.5	15.76	34.8
NWL	2.375	60.3	2.750	69.9	23.55	52
NTW	2.525	64.2	2.875	73.0	22.83	50.4
HWL	3.062	77.8	3.500	88.9	34.88	77
PWL	4.062	103.2	4.625	117.5	48.02	106

CORING BIT DATA

Size	Core Diameter		Hole Diameter	
	inch	mm	inch	mm
AWL	1.062	27.0	1.890	48.0
ATW	1.185	30.1	1.890	48.0
BWL	1.432	36.5	2.360	60.0
BTW	1.656	42.0	2.360	60.0
NWL	1.875	47.6	2.980	75.7
NTW	2.205	56.0	2.980	75.7
HWL	2.500	63.5	3.782	96.0
PWL	3.345	85.0	4.827	122.6

**BOREHOLE
SURVEY INSTRUMENTS,
ALIGNMENT SYSTEMS,
CORE ORIENTATION,
DIRECTIONAL CORE BARREL**



www.devico.com

